



BOLTAR FUNDATIE BF50x20



SIGICOM S.R.L.
Bistrita, str. Lavandei nr.7,
jud. Bistrita-Nasaud
19

SR EN 771-3+A1/2015
BF50x20
In structura fundatiilor



Utilizare preconizata: in structura fundatiilor.

Performante declarate conform -Declaratia de performanta Nr.106-2021 :

Caracteristici	Performante obtinute	Specificatia tehnica armonizata
Dimensiuni	L=50;l=20;h=20 cm	EN 772-16:2011
Rezistenta la incovoiere	5,26 N/mm ² ,	SR EN 15435:2008
Absortia de apa	8,56 g/ m ² *s	SR EN 772-11:2001
Rezistenta la foc	Euroclasa A1	EN 1350-1+A1:2010
Densitate absoluta	1790 kg/mc	SR EN 772-13:2001
Densitate aparenta	900 kg/mc	SR EN 772-13:2001
Determinarea procentuala a ariei golurilor	52,35 %	SR EN 772-2:2000+A1:2006
Determinarea planeitatii	1 mm	EN 772-20:2003+A1:2006
Coeficient de difuzie al vaporilor de apa tabelar	5/10 μ	EN1745;EN ISO 12572
Determinarea rezistentei la inghet - dezghet	Rc=15,68%	SR EN 771-3+A1/2015

